



DESCRIPTION

PEAK Global® LifeTime® Antifreeze + Coolant features an advanced organic acid technology that provides guaranteed lifetime protection for as long as you own your vehicle!* Its specially-engineered formula will provide maximum protection against damaging rust and corrosion in all automobiles, and light/medium and heavy duty trucks worldwide, regardless of make, model, year or original antifreeze color.

FEATURES & BENEFITS

- Provides guaranteed lifetime protection for as long as you own your vehicle when a complete cooling system flush and fill is performed and specified maintenance followed†
- Formulated for use in all American, Asian, and European vehicles
- Features a proprietary non 2-EH formula that is borate, nitrite, amine and silicate-free
- Amber color will not change the current antifreeze color when used for topping off

APPLICATIONS

Engineered for use in all passenger cars, SUVs, motorcycles, and light/medium and heavy duty trucks, regardless of make, model, year or antifreeze/coolant in the system.

†Requires a complete cooling system flush and fill and regular manufacturer-specified maintenance.



RECOMMENDED FOR USE WHERE THE FOLLOWING SPECIFICATIONS ARE CITED‡:

- Chrysler MS-7170
- Chrysler MS-9769
- Chrysler MS-12106
- Ford ESE M97B44-A
- Ford WSS-M97B44-D
- Ford WSS-M97B51-A1
- Ford WSS-M97B57-A1
- GM 1825M
- GMW3420

MEETS OR EXCEEDS THE FOLLOWING SPECIFICATIONS:

- ASTM D3306
- ASTM D4985
- ASTM D6210

‡ Always confirm product selected is consistent with the OEM's recommendation for equipment operating conditions, changeover intervals and customer's maintenance practices. This product has not been tested nor approved by Ford Motor Company, Chrysler/FCA, and General Motors LLC.

FREEZE/BOIL PROTECTION CHART

Coolant/Water Ratio†	PROTECTION FROM	
	Freezing Down to	Boiling Up to*
50/50	-34°F (-36°C)	265°F (129°C)
60/40	-62°F (-52°C)	270°F (132°C)
70/30	-84°F (-64°C)	276°F (135°C)

*At sea level atmospheric pressure with 15 lb. pressure cap. The boiling point decreases about 2°F per 1,000 feet of altitude and increases about 2.5°F per pound developed in the system.

†Limit coolant concentration for heavy duty applications to no more than 60%



PROPERTIES	ASTM Method	TYPICAL VALUES		ASTM D3306 Limits
		CONCENTRATE	PREDILUTED (50/50)	
Appearance/Color	Visual	Amber	Amber	Distinctive
pH	D1287	8.3 ²	8.3	7.5-11.0
Specific gravity	D1122	1.1130	1.077	1.110-1.145 ¹ /1.065 min ²
Boiling point, °F (°C) ³	D1287	325 (162.8)	229 (109)	226 (108) min
Freezing point, °F (°C)	D1177	--	-37.8 (-38.8)	-34 (-36.4) max
Effect on Automotive finish	D1882	No Effect	No Effect	No Effect
Total water, mass %	D1123	<5	50	5 max ¹
Ash content, mass %	D1119	<5	<2.5	5 max ¹ /2.5 max ²
Chloride, ppm	D3634	<25	<25	25 max

¹For concentrate product only, ²Prediluted (50/50) only, ³Unpressurized

SHIPPING INFORMATION

CONCENTRATE



PXA0B1
55 Gallon
Concentrate Drum
0-74804-03397-7

PXA0B3
1 Gallon
Concentrated Bottle
0-74804-00407-6

50/50 PREDILUTED



PXAB51
55 Gallon
50/50 Drum
0-74804-03351-9

PXAB53
1 Gallon
50/50 Bottle
0-74804-00243-0

To order, please call Old World Industries, LLC Customer Service at 1-800-323-8755.

Part #	Unit	Pack/Size	Dimensions	Unit Wt (lbs)	Units per Pallet	Pallets per Truck	Pallet Weight**
PXA0B3	Case	6/1 gal	15.8" L x 12.6" W x 12.25" H	60	36	20	2,298
PXAB53	Case	6/1 gal	15.8" L x 12.6" W x 12.25" H	54	36	20	2,082
PXAB51	Drum	55 gal	23.5" dia. x 34.5"	520	4	20	2,277
PXA0B1	Drum	55 gal	23.5" dia. x 34.5"	495	4	20	2,177

**Includes pallet weight of 50 lbs each

ADDITIONAL INFORMATION

Testing Requirements: For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

Storage Recommendations: PEAK Global Antifreeze/Coolant can be stored in original container at ambient temperature and limited periods of exposure to temperatures above 95°F (35°C) for 3-5 years, provided the container remains sealed. Product should be agitated before dilution or use.

Safety and Environmental Guidance: PEAK Global Antifreeze/Coolant is based on virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestions of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from peakauto.com. Always dispose of used coolant in accordance with local, state and Federal guidelines.

Old World Industries, LLC
Northbrook, IL 60062 • 800-323-5440
Peakauto.com

