



## DIESEL FUEL ADDITIVE

# DIESEL ANTI-GEL

## WITH CETANE BOOST & INJECTOR CLEANER



### DESCRIPTION:

BLUE DIESEL ANTI-GEL is a multifunctional diesel additive that is specifically designed to work in harsh, cold weather environments. It contains a unique blend of Cold Flow Improvers that lower the pour point up to 39°F and reduce the CFPP up to 30°F. BLUE DIESEL ANTI-GEL is designed with a patented detergent additive technology that keeps injectors found in new generation High-Pressure Common Rail (HPCR) injection systems clean.

### BENEFITS:

- Prevents fuel gelling in extremely cold weather
- Wax Anti-Settling Agents (WASA) help prevent heavy wax from settling in fuel tanks
- Improves cetane by up to 4 numbers, for better performance
- Improves lubricity to protect fuel injectors and pumps against premature wear
- De-icing chemistry reduces filter plugging due to moisture
- Patented diesel detergent technology keeps fuel injectors clean and optimizes fuel economy, while providing efficient combustion and reduced emissions
- Effective in all diesel fuels, including biodiesel blends
- Contains less than 15 PPM Sulfur

### PROPERTIES:

### TYPICAL VALUES

Form	Liquid
Appearance	Colorless Amber
Odor	Petroleum-like
Flash Point	69 °C (156 °F)
Specific Gravity	0.89 @ 15.6 °C (60.1 °F)
Viscosity, kinematic	1.68 mm <sup>2</sup> /s @ 40 °C (104 °F)

### SHIPPING INFO:

Description	16oz.	32oz.	64oz.
<b>Part Number</b>	BDDAG16	BDDAG32	BDDAG64
<b>Unit UPC</b>	0-74804-05926-7	0-74804-05927-4	0-74804-05928-1
<b>Case UPC</b>	0-74804-15926-4	0-74804-15927-1	0-74804-16697-2
<b>Case SCC-14</b>	1-00-74804-05926-4	1-00-74804-05927-1	1-00-74804-06697-2
<b>Case Weight/Cube</b>	10 lbs/0.45 cu. ft.	25 lbs/0.90 cu. ft.	12.50 lbs/0.45 cu. ft.
<b>Pack/Unit Case</b>	9	12	3
<b>Unit Dimensions</b>	4.15"l x 1.9"w x 8.74"h	4.28"l x 2.58"w x 9.76"h	6.75"l x 3.78"w x 8.9"h
<b>Case Dimensions</b>	13.0625"l x 6.25"w x 9.625"h	13.5625"l x 10.8125"w x 10.5625"h	11.875"l x 6.94"w x 9.875"h
<b>Units/Cases per Pallet</b>	945 units/105 cases (2,310 cases/truck)	528 units/44 cases (968 cases/truck)	240 units/80 cases (1760 cases/truck)
<b>Cases/Rows High</b>	21/5	11/4	20/4
<b>Units per Truck</b>	20,790	11,616	5,280
<b>Truckload Weight</b>	22 pallets/truck - 24,200 lbs.	22 pallets/truck - 25,300 lbs.	22 pallets/truck - 22,000 lbs.
<b>Pallet Size</b>	48"l x 40"w x 53"h	48"l x 40"w x 47.1"h	47"l x 36"w x 44"h
<b>Pallet Weight</b>	1,100 lbs.*	1150 lbs.*	1000 lbs. *

(\* Includes Pallet Wt.: 20 @ 50 lbs. ea. = 1,000 lbs. Product Liability Information/Safety Data Sheet available upon request.

### TREATMENT RATES

Diesel Fuel Additive Required	Gallons of Diesel Fuel
16oz.	80
32oz.	160
64oz.	320

Treat rates may vary due to regional fuel characteristics. Please contact your PEAK representative for recommendations.



**DIESEL FUEL QUALITY IS IMPORTANT.  
KEEP YOUR MACHINES AND YOUR  
PEOPLE RUNNING**

Distributed by Old World Industries, LLC Northbrook, IL 60062  
800.323.5440



**CHEMISTRY THAT DRIVES COMMERCE™**  
©2018 PEAK, the PEAK mountain graphic, Blue & the Drop Graphic are Registered Trademarks of Old World Industries, LLC.