



DIESEL FUEL ADDITIVE

EMERGENCY DIESEL THAW

RELIQUEFIER AND DE-ICER



DESCRIPTION:

BLUE EMERGENCY DIESEL THAW is designed to quickly reliquefy gelled fuel and thaw frozen fuel filters in extremely cold environments. BLUE EMERGENCY DIESEL THAW prevents ice crystal build up in fuel lines and filter by dispersing moisture. This is an ideal solution for fuel tanks that have not yet been winterized and encounter unexpected freezing conditions. BLUE EMERGENCY DIESEL THAW does not prevent fuel gelling - use BLUE DIESEL ANTI-GEL as a preventative measure to keep fuel from gelling.

BENEFITS:

- De-ices frozen fuel and filters
- Reliquefies gelled fuel
- Prevents fuel and filter icing
- Removes water from fuel system
- Effective in all diesel fuels, including Ultra Low Sulfur Diesel (ULSD), biodiesel and biodiesel blends

PROPERTIES:

TYPICAL VALUES

Physical state	Liquid
Color	Amber Brown
Odor	Petroleum-like odor
Boiling point	106 °C (223 °F)
Flash point	25 °C (77 °F)
Specific Gravity	0.84 @ 15.6 °C (60.1 °F)
Density	7 lbs/gal @ 15.6 °C (60.1 °F)
Solubility	Water: Insoluble
Viscosity, kinematic	0.88 mm ² /s @ 40 °C (104 °F)

SHIPPING INFO:

Description	16oz.	32oz.
Part Number	BDEDT16	BDEDT32
Unit UPC	0-74804-05929-8	0-74804-05930-4
Case UPC	0-74804-15929-5	0-74804-15930-1
Case SCC-14	1-00-74804-05929-5	1-00-74804-05930-1
Case Weight/Cube	10 lbs/0.45 cu. ft.	25 lbs/0.90 cu. ft.
Pack/Unit Case	9	12
Unit Dimensions	4.15"l x 1.9"w x 8.74"h	4.28"l x 2.58"w x 9.76"h
Case Dimensions	13.0625"l x 6.25"w x 9.625"h	13.5625"l x 10.8125"w x 10.5625"h
Units/Cases per Pallet	945 units/105 cases (2,310 cases/truck)	528 units/44 cases (968 cases/truck)
Cases/Rows High	21/5	11/4
Units per Truck	20,790	11,616
Truckload Weight	22 pallets/truck - 24,200 lbs.	22 pallets/truck - 25,300 lbs.
Pallet Size	48"l x 40"w x 53"h	48"l x 40"w x 47.1"h
Pallet Weight	1,100 lbs.*	1,150 lbs.*

(*) Includes Pallet Wt.: 20 @ 50 lbs. ea. = 1,000 lbs. Product Liability Information/Safety Data Sheet available upon request.

TREATMENT RATES

Diesel Fuel Additive Required	Gallons of Diesel Fuel
16oz.	50
32oz.	100

Treat rates may vary due to regional fuel characteristics. Please contact your PEAK representative for recommendations.



**DIESEL FUEL QUALITY IS IMPORTANT.
KEEP YOUR MACHINES AND YOUR
PEOPLE RUNNING**

Distributed by Old World Industries, LLC Northbrook, IL 60062
800.323.5440



CHEMISTRY THAT DRIVES COMMERCE™
©2018 PEAK, the PEAK mountain graphic, Blue & the Drop Graphic are Registered Trademarks of Old World Industries, LLC.