



DIESEL FUEL ADDITIVE

CLEAR GUARD™

FUEL POLISHER AND WATER DISPERSANT



DESCRIPTION:

BLUE CLEAR GUARD is an advanced, proprietary diesel fuel treatment that provides superior tank protection by dispersing water and reducing the chance of microbial contamination. It will also stabilize the diesel fuel, ensuring that the fuel stays fresh.

BENEFITS:

- Disperses and cleans up contaminants
- Fast-acting - absorbs excess water fast
- Helps eliminate conditions conducive to microbial growth
- Keeps fuel fresh and provides maximum long-term storage stability
- Protects against fuel tank corrosion
- Removes slime
- Does not contain low molecular alcohols that will harm critical engine parts
- Prevents aging of fuel
- Prevents premature fuel filter plugging
- Safe for use in all diesel engines
- Effective in Ultra Low Sulfur Diesel, renewable diesel, biodiesel, and biodiesel blends up to and including B20

PROPERTIES:

TYPICAL VALUES

Appearance	Colorless Amber
Form	Liquid
Odor	Petroleum-like
Specific Gravity	0.85 @ 15.6 °C (60.1 °F)
Solubility	Water: Insoluble
Flash Point	67 °C (153 °F)
Density	7.10 lbs/gal @ 15.6 °C (60.1 °F)
Viscosity, kinematic	1.55 mm ² /s @ 40 °C (104 °F)
Boiling Point	136 °C (277 °F)

SHIPPING INFO:

Description	32oz.	64oz.
Part Number	BDCGD32	BDCGD64
Unit UPC	0-74804-06441-4	0-74804-06442-1
Case UPC	0-74804-16441-1	0-74804-16698-9
Case SCC-14	1-00-74804-06441-1	1-00-74804-06698-9
Case Weight/Cube	25 lbs/0.90 cu. ft.	12.50 lbs/0.45 cu. ft.
Pack/Unit Case	12	3
Unit Dimensions	4.28"l x 2.58"w x 9.76"h	6.75"l x 3.78"w x 8.9"h
Case Dimensions	13.5625"l x 10.8125"w x 10.5625"h	11.875"l x 6.94"w x 9.875"h
Units/Cases per Pallet	528 units/44 cases (968 cases/truck)	240 units/80 cases (1760 cases/truck)
Cases/Rows High	11/4	20/4
Units per Truck	11,616	5,280
Truckload Weight	22 pallets/truck - 25,300 lbs.	22 pallets/truck - 22,000 lbs.
Pallet Size	48"l x 40"w" x 47.1"h	47"l x 36"w" x 44"h
Pallet Weight	1150 lbs.*	1000 lbs.*

(* Includes Pallet Wt.: 20 @ 50 lbs. ea. = 1,000 lbs. Product Liability Information/Safety Data Sheet available upon request.

TREATMENT RATES

Diesel Fuel Additive Required	Gallons of Diesel Fuel
32oz.	125
64oz.	250

Treat rates may vary due to regional fuel characteristics. Please contact your PEAK representative for recommendations.



**DIESEL FUEL QUALITY IS IMPORTANT.
KEEP YOUR MACHINES AND YOUR
PEOPLE RUNNING**

Distributed by Old World Industries, LLC Northbrook, IL 60062
800.323.5440



peakauto.com

CHEMISTRY THAT DRIVES COMMERCE™

©2018 PEAK, the PEAK Mountain Graphic, Blue, the Drop Graphic and CLEAR GUARD are Registered Trademarks of Old World Industries, LLC.