



## DESCRIPTION:

PEAK® FULL SYNTHETIC MULTI-VEHICLE DEXRON® VI/MERCON® LV AUTOMATIC TRANSMISSION FLUID is specially formulated with a unique combination of low temperature, low volatility synthetic base fluid and advanced additive technology to ensure the highest performance in the latest automatic transmissions. This premium quality product meets, or exceeds, the frictional and wear requirements of most automatic transmissions, regardless of age, and is approved by General Motors and Ford in transmissions specifying either DEXRON® VI and MERCON® LV automatic transmission fluid. This is truly the most diverse automatic transmission fluid available. Suitable for use in all the applications listed.

## BENEFITS:

- Superior foam control for smooth gear changes
- Protects against pitting
- Excellent wear protection
- Excellent oxidation stability
- High shear stability

## APPLICATION:

PEAK® FULL SYNTHETIC MULTI-VEHICLE DEXRON® VI/MERCON® LV ATF is recommended where the following specifications are required:

GM DEXRON® VI, III(H), III(G), II, IIE  
 Chrysler® ATF+4 (MS 9602), ATF+3 (MS 7176E), ATF+2, ATF  
 Ford® MERCON® LV (FF-WSS-M2C-938A/SF, XT-10 QLV), MERCON®  
 See complete list of supported applications on other side.

Do not use in applications specifying Ford MERCON® V, or MERCON® SP. Not a suitable replacement fluid in Continuously Variable Transmissions (CVT) or Dual Clutch Transmissions (DCT).

## SHIPPING INFORMATION:

Pack	6/1 Quart	4/1 Gallon	55 Gallon Drum
Unit Weight (lbs.)	2.1	8.2	450
Case/Pallet Weight*	12.3/2,108	32.7/1,750	1,850
Units per Pallet	1,008	208	4
Cases per Pallet	168	52	-
Units per Truck	21,168	4,992	84
Cases/Pallets per Truck	3,528/21	1,248/24	21
Case Size (inches)	8.9 x 7.4 x 8.8	15.4 x 8.4 x 11.9	-
Cases per row/Rows high	24/7	13/4	-
Pallet Size (inches)	48 x 40 x 72.3	40 x 48 x 55.6	46 x 48 x 40.5

(\* Including pallet weight of 50 lbs.)

## PRODUCT INFORMATION:

Test (Method)	FULL SYN MV ATF	FULL SYN MV ATF	FULL SYN MV ATF
Appearance (ASTM D-1500)	Red	1 Quart Part Number	PVTS076
Viscosity Index (ASTM D-2270)	151	1 Gallon	PVTS09
Viscosity		55 gallon Drum	PVTS01
'@ 40 °C, cSt (ASTM D-445)	29.3	Bulk	PVTFD0
'@ 100 °C, cSt (ASTM D-445)	5.92		
Brookfield Viscosity (ASTM D-2893) (cPat: 40 °C)	10,300		
	<b>PVTS076</b>	<b>PVTS09</b>	<b>PVTS01</b>
Individual UPC Code	0-74804-04927-5	0-74804-05274-9	0-74804-05302-9
Case UPC Code	0-74804-14927-2	0-74804-15274-6	-
Case SCC-14 Code	1-00-74804-04927-2	1-00-74804-05274-6	-



Suitable for use in the following applications:

#### Application / Performance

Acura ATF-Z1  
Aisin Warner JWS 3309 (T-IV) & JWS 3324 (WS), AW-1  
Allison C-3 & C-4  
American Motors ATF +3 (MS7176-E), ATF +4 (MS9602)  
ATF Claim Set  
ATF RED 1, RED 1K  
Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A)  
Audi/VW G 052 025-A2  
Audi/VW G 052 162 (ZF Lifeguardfluid 5) (ZF No. S671 090 170)  
Audi/VW G 052 162-A1/A2  
Audi/VW G 052 990  
Audi/VW G 053 025-A2  
Audi/VW G 055 025 A2 (JWS 3309)  
Audi/VW G 055 540 (A2)  
Audi/VW G 060 162 (ZF Lifeguardfluid 8) (ZF No. S671 090 312)  
BMW 7045E  
BMW ETL 8072B  
BMW JWS 3309 (T-IV)  
BMW LA2634  
BMW LT71141 (ZF 5 HP 18FL/19FL/24A)  
BMW MINI  
BMW ZF 5HP18FL, 5HP24, 5HP30  
Bosch TE-ML 09  
CAT TO-2  
Chrysler ATF+, +2, +3 (MS 7176E), +4 (MS 9602)  
Chrysler/Dodge MOPAR AS 68 RC (T-IV), JWS 3309  
Chrysler/Dodge/Jeep 68043742AA  
Daewoo LT 71141  
Daihatsu AMMIX ATF D-II  
Daihatsu AMMIX ATF D-III SP  
Esso LT 71141  
FIAT T-IV type, JWS 3309  
Ford ESP-M2C166H, XL-12  
Ford FNR5  
Ford MERCON®  
Ford MERCON® LV (FF-WSS-M2C-938A/SF, XT-10 QLV)  
Ford WSS M2C 138CJ, 166H  
Ford WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309  
Fuso ATF-A4  
Fuso ATF-II  
Fuso ATF-SPIII  
GM DEXRON®-II  
GM DEXRON®-IID  
GM DEXRON®-IIE  
GM DEXRON®-IIIG  
GM DEXRON®-IIIH  
GM DEXRON®-VI  
GM TASA  
GM/GMC/Opel/Saturn 88863400  
GM/GMC/Opel/Saturn 88863401  
GM/GMC/Opel/Saturn AW1  
GM9986195 (Aisin AW, JWS 3309)  
Hino Blue Ribbon ATF  
Honda ATF-Z1 (except in CVTs)  
Honda DW-1

#### Application / Performance

Honda Type 3.1  
Hyundai/Kia 040000C90SG  
Hyundai/Kia Dex-II/ SP-II  
Hyundai/Kia JWS 3314  
Hyundai/Kia NWS 9638  
Hyundai/Kia SP-III  
Hyundai/Kia SP-IV  
Hyundai/Kia SP-IV M (SP4-M)  
Hyundai/Kia SP-IV-RR  
ISUZU BESCO ATF SP  
ISUZU BESCO ATF-II  
ISUZU BESCO ATF-III  
ISUZU SCS Fluid  
Jaguar ATF 3403 JLM20238,  
Jaguar ATF 3403 M115, ATF 3403-M115,  
Jaguar ATF LT71141, ZF 5HP24  
Jaguar JLM20238  
JASO M315-2013 1A\*  
JASO M315-2013 1A-LV  
JASO M315-2013 2A\*  
JEEP ATF+3, +4  
KIA ATF SP-II, SP-III, SP-IV, SP-IVM, Red 1  
Lexus JWS 3309  
MAN 339A  
MAZDA ATF 3317  
Mazda ATF D-II  
Mazda ATF F-1  
Mazda ATF FZ  
Mazda ATF M-III  
Mazda ATF M-V  
Mazda ATF N-1  
Mazda ATF S-1  
Mercedes MB 223.2, 236.1, 236.2, 236.10,  
Mercedes MB 236.12, 236.41, 236.5, 236.6,  
236.7  
MINI COOPER T-IV  
Mitsubishi Diaqueen ATF PA  
Mitsubishi Diaqueen AW  
Mitsubishi Diaqueen J2  
Mitsubishi Diaqueen J3  
Mitsubishi Diaqueen SK  
Mitsubishi Diaqueen SP-II  
Mitsubishi Diaqueen SP-III  
Mitsubishi Diaqueen SP-IV  
NAG 1 (Chrysler, Jeep, Cherokee)  
Nissan Matic Fluid C  
Nissan Matic Fluid D  
Nissan Matic Fluid J  
Nissan Matic Fluid K  
Nissan Matic Fluid S  
Opel (all vehicles)  
Peugeot ZF 4HP20  
Porsche ATF 3403-M115,  
Porsche T-IV (JWS 3309)  
Porsche ZF 5HP19FL, ZF 5HP20, LT71141

#### Application / Performance

Renault DPO/AL4  
Renault Samsung SATF-D  
Saab 93 160 393  
Saab 93 165 147  
Saab T-IV (JWS 3309)  
Saturn T-IV (JWS 3309)  
Scion (all vehicles)  
Shell 3403, M115, LA 2634  
Shell L 12108  
Subaru ATF  
Subaru ATF 5AT  
Subaru ATF, ATF HP  
Subaru DEXRON®-II  
Suzuki AT OIL 5D06  
Suzuki ATF 2326  
Suzuki ATF 2384K  
Suzuki ATF 3314  
Suzuki ATF 3317  
Suzuki ATF AW-1  
Suzuki JWS 3309  
Texaco 7045-E  
Texaco 8072B  
Texaco N402  
Toyota ATF D-II  
Toyota ATF D-III  
Toyota ATF T-III  
Toyota ATF T-IV  
Toyota ATF WS  
Vickers M2950-S, I-286-S  
Voith 55.6335.xx (G607)  
Volvo 97325  
Volvo 97335  
Volvo CE 97340  
Volvo PN 1161521  
Volvo PN 1161540/1161640  
VW 5 HP (ZF 5 HP 30)  
VW 5HP (18FL, 30)  
VW 5HP (19FL, 24A)  
VW G 052 162 (ZF Lifeguardfluid 5)  
VW G 060 162 (ZF Lifeguardfluid 8)  
VW G055 540 (A2)  
VW G-055-025 A2 (JWS 3309)  
VW TL 521 62  
ZF 8 speed transmissions  
ZF all 3 & 4 speed transmission  
ZF TE-ML 05L  
ZF TE-ML 09  
ZF TE-ML 11A, 11B  
ZF TE-ML 21L

\*Caution, does not meet visc spec



Distributed by Old World Industries, LLC Northbrook, IL 60062

☎ 800.323.5440 [www.peakauto.com](http://www.peakauto.com)

©2017 PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, LLC.